

46/1

Norm UNI EN ISO 20344:2012, UNI EN ISO 20345:2012
Security category S3
Additional requirements A, E, HRO, P, SRC, WRU



PRODUCT DESCRIPTION:
Mid-boots type "B", with suede leather upper. Airnet® highly breathable and absorbent 3D mesh lining. Composit® toe cap, Kevlar anti-perforation insole. Lacing passing through holes or eyelets. PU outsole + rubber tread, anti-static, oil and slip resistant. "Ago" working.

Lining	3D Fabric: <i>AIRNET® - Highly breathable and absorbent three-dimensional mesh fabric</i>
Size	Unisex 36-47
Processing	<i>AGO: The Ago processing is the most common because it makes the shoe flexible and light. The processing consists of joining the upper to the sole through glues, avoiding the use of other joints that stiffen the structure and lead to a loss of comfort in the foot</i>
Sector	Outdoor environments, Indoor environments, Manufacturing Industries, Mechanical industries, Textile industries
Footwear type	B (over the ankle)
Upper	Suede: <i>Soft calfskin leather</i>
Insole	Anti-perforation: <i>Protect the foot against possible shoe perforations caused by the presence of perforating material on the floor</i>
Toe cap	Composite: <i>resistant up to 200J. Protective strip for fingers' comfort</i>
Group	JOGGING
Outsole	Danilo: <i>Soft cushioning and antistatic polyurethane midsole. Heat resistant rubber tread with high slip resistance even on inclined surfaces.</i>
Protection	Toe cap and anti-perforation insole

PRODUCT TECHNICAL SHEET



Date 17/05/2024

