

M16

Security category

O3

Additional requirements A, CI, E, FO, HRO, P, SRC, WR, WRU



PRODUCT DESCRIPTION:

Waterproof full grain leather upper and textile inserts. Waterproof PTFE membrane lining. Ultralight phylon and rubber sole with stabiliser. Transparent TPU protection. textile anti-perforation UNI EN ISO 12568: 2012. "Ago" processing.

Upper	Leather: <i>Water repellent full-grain leather 1.8-2.0 mm</i> , Fabric
Lining	PTFE membrane lining: <i>WINDTEX - Bi-component microporous PTFE membrane with high waterproofness, perspiration and resistance (400gr)</i>
Outsole	<i>ENERGY SHIELD: is a new type of outsole specifically designed for maximum support and comfort. The double action of ultra-light Phylon and soft PU, allows maximum damping. The plastic stabilizing insert protects the foot thanks to a maximum support of the arch. Rubber tread ensures maximum slip resistance and anti-abrasion.</i>
Insole	Anti-perforation: <i>Protect the foot against possible shoe perforations caused by the presence of perforating material on the floor</i>
Allacciatura	Elastica

PRODUCT TECHNICAL SHEET



Date 19/05/2024



The data shown on this sheet are subject to change without notice due to the evolution of materials and products.
All rights reserved. All other product and company names are trademarks of their respective owners.
No part of this sheet may be reproduced in any form or means, for any use.