

# 39/2

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022

Security category S3

Additional requirements A, E, HRO, PL, SR, WPA



### PRODUCT DESCRIPTION:

Low shoe type "A". Suede leather upper and fabric stripes upper. Highly breathable and absorbent Airnet® 3D mesh lining. Composit® toe cap, Kevlar anti-perforation insole. Lacing passing through holes or eyelets. Antistatic, oil and slip resistant PU outsole + rubber tread. "Ago" working.

Lining	3D Fabric: <i>AIRNET® - Highly breathable and absorbent three-dimensional mesh fabric</i>
Size	Unisex 36-49
Processing	<i>AGO: The Ago processing is the most common because it makes the shoe flexible and light. The processing consists of joining the upper to the sole through glues, avoiding the use of other joints that stiffen the structure and lead to a loss of comfort in the foot</i>
Sector	Indoor environments, Manufacturing Industries, Mechanical industries, Textile industries
Footwear type	A (low)
Upper	Suede: <i>Soft calfskin leather</i>
Insole	Anti-perforation: <i>Protects the foot against possible injury caused by the presence of perforating material on the floor.</i>
Toe cap	Composite: <i>resistant up to 200J. Protective strip for toe comfort.</i>
Group	JOGGING
Outsole	Danilo: <i>Soft cushioning and antistatic polyurethane midsole. Heat resistant rubber tread with high slip resistance even on inclined surfaces.</i>
Protection	Toe cap and anti-perforation insole



# PRODUCT TECHNICAL SHEET



Date 04/04/2025



The data shown on this sheet are subject to change without notice due to the evolution of materials and products.  
All rights reserved. All other product and company names are trademarks of their respective owners.  
No part of this sheet may be reproduced in any form or means, for any use.