


RUN - SUEDE

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022

Security category S3

Additional requirements A, E, FO, HI, HRO, PL, SR



PRODUCT DESCRIPTION:

Black suede leather upper with yellow Cordura inserts and highly breathable 3D Airnet® textile lining. Composit® toecap. Kevlat textile anti-perforation UNI EN ISO 12568: 2012. Ultralight phylon and PU sole + slip resistant rubber tread with anti-torsion stabiliser. "Ago" processing.

Upper	Pelle scamosciata e cordura: <i>Pelle scamosciata idrorepellente e tessuto cordura traspirante</i>
Lining	3D Fabric: <i>AIRNET® - Highly breathable and absorbent three-dimensional mesh fabric</i>
Toe cap	Composite: <i>resistant up to 200J. Protective strip for toe comfort.</i>
Insole	Anti-perforation: <i>Protects the foot against possible injury caused by the presence of perforating material on the floor.</i>
Processing	AGO: <i>The Ago processing is the most common because it makes the shoe flexible and light. The processing consists of joining the upper to the sole through glues, avoiding the use of other joints that stiffen the structure and lead to a loss of comfort in the foot</i>
Outsole	ENERGY SHIELD: <i>is a new type of outsole specifically designed for maximum support and comfort. The double action of ultra-light Phylon and soft PU, allows maximum damping. The plastic stabilizing insert protects the foot thanks to a maximum support of the arch. Rubber tread ensures maximum slip resistance and anti-abrasion.</i>
Size	Unisex 36-49
Protection	Toe cap and anti-perforation insole
Sector	Outdoor environments, Indoor environments, Manufacturing Industries, Mechanical industries
Footwear type	A (low)



PRODUCT TECHNICAL SHEET



Date 04/04/2025

