

POWER

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022
Security category S3
Additional requirements A, CI, E, FO, HI, HRO, PL, SR, WPA, WR



PRODUCT DESCRIPTION:
Ankle footwear with full grain leather upper and Cordura inserts. Waterproof and breathable PTFE membrane lining. Ultralight ENERGY SHIELD sole with a double layer of phylon, stabiliser and antistatic and slip resistant rubber tread. Composit® toecap, Kevlar textile anti-perforation insole. "Ago" processing. Available colours: black/black and black/yellow

Upper	Leather and fabric inserts: <i>Water repellent full-grain leather and highly breathable cordura fabric</i>
Lining	PTFE membrane lining: <i>WINDTEX - Bi-component microporous PTFE membrane that provides high waterproofness, breathability and resistance</i>
Outsole	ENERGY SHIELD: <i>is a new type of outsole specifically designed for maximum support and comfort. The double action of ultra-light Phylon and soft PU, allows maximum damping. The plastic stabilizing insert protects the foot thanks to a maximum support of the arch. Rubber tread ensures maximum slip resistance and anti-abrasion.</i>
Toe cap	Composite: <i>resistant up to 200J. Protective strip for toe comfort.</i>
Insole	Anti-perforation: <i>Protects the foot against possible injury caused by the presence of perforating material on the floor.</i>
Processing	AGO: <i>The Ago processing is the most common because it makes the shoe flexible and light. The processing consists of joining the upper to the sole through glues, avoiding the use of other joints that stiffen the structure and lead to a loss of comfort in the foot</i>
Size	Unisex 36-49
Footwear type	B (over the ankle)
Sector	Outdoor environments, Civil Protection, Rescue
Protection	Toe cap and anti-perforation insole

PRODUCT TECHNICAL SHEET



Date 12/08/2025



PRODUCT TECHNICAL SHEET



Date 12/08/2025

