PRODUCT TECHNICAL SHEET



Date 07/06/2025

RICKY-23

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022

Security category S1P

Additional requirements A, E, FO, HRO, PL, SR



PRODUCT DESCRIPTION:

Low shoe type "A". Suede leather upper with anti-abrasion inserts on toe and heel. Highly breathable 3D Airnet® textile lining. Composit® toecap. Kevlar textile anti-perforation UNI EN ISO 12568:2022. "SOCKSHOE" technology for confortable and easy donning and doffing, like a sock. Ultralight phylon and PU sole + slip resistant rubber tread with anti-torsion stabiliser. "Ago" processing. Available in black/yellow and black/green.

Upper Suede: Soft calfskin leather

Lining 3D Fabric: AIRNET® - Highly breathable and absorbent three-dimensional mesh

fabric

Toe cap Composite: resistant up to 2001. Protective strip for toe comfort.

Insole Anti-perforation: Protects the foot against possible injury caused by the

presence of perforating material on the floor.

Processing AGO: The Ago processing is the most common because it makes the shoe

flexible and light. The processing consists of joining the upper to the sole

through glues, avoiding the use of other joints that stiffen the structure and lead

to a loss of comfort in the foot

Outsole ENERGY SHIELD: is a new type of outsole specifically designed for maximum

support and comfort. The double action of ultra-light Phylon and soft PU, allows maximum damping. The plastic stabilizing insert protects the foot thanks to a maximum support of the arch. Rubber tread ensures maximum slip resistance

and anti-abrasion.

Size Unisex 36-49

Protection Toe cap and anti-perforation insole

Sector Outdoor environments, Indoor environments, Manufacturing Industries,

Mechanical industries

Footwear type A (low)

Tecnologia SOCKSHOE TECHNOLOGY: Provides sock-like fit and facilitates quick removal

PRODUCT TECHNICAL SHEET



Date 07/06/2025



PRODUCT TECHNICAL SHEET



Date 07/06/2025

