

PM002/PA/SK

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022

Security category S3

Additional requirements A, E, HRO, M, PL, SR, WPA



PRODUCT DESCRIPTION:

Low shoe type "A". Water-repellent full-grain leather metatarsal protection and upper. Leather lining. Steel toe cap, Kevlar anti-perforation insole, lacing passing through metal eyelets or metal D-ring hooks. Metatarsal protection attached with double stitching and 3 rivets. Single-layer rubber insole and rubber outsole. "Ideal" processing.

Lining	Leather: <i>Soft leather</i>
Outsole	ROCCIA: <i>Energy absorbing, antistatic, contact heat, fuel, oil and slip resistant rubber outsole.</i>
Size	Unisex 36-49
Processing	IDEAL: <i>The leather upper is prepared by glueing and pressing the outer edges onto a midsole and is then stitched using a machine called "rapid". The thread is passed through a boiler with molten pitch to totally waterproof the thread and holes.</i>
Protection	Toe cap, anti-perforation midsole and metatarsal protection
Sector	Steelwork, Outdoor environments, Building, Electricians, Foundry, Manufacturing Industries, Mechanical industries, Welders
Footwear type	A (low)
Upper	Leather: <i>Water repellent full-grain leather 1.8-2.0 mm</i>
Insole	Anti-perforation: <i>Protects the foot against possible injury caused by the presence of perforating material on the floor.</i>
Toe cap	Steel: <i>up to 200J</i>

PRODUCT TECHNICAL SHEET



Date 02/09/2025



The data shown on this sheet are subject to change without notice due to the evolution of materials and products.
All rights reserved. All other product and company names are trademarks of their respective owners.
No part of this sheet may be reproduced in any form or means, for any use.

PRODUCT TECHNICAL SHEET



Date 02/09/2025

