PRODUCT TECHNICAL SHEET



Date 30/11/2025

OW23M

Norm UNI EN ISO 20344:2022, UNI EN ISO 20345:2022

Security category S1PLM

Additional requirements A, E, FO, HRO, M, PL, SR, WPA

















PRODUCT DESCRIPTION:

Calzatura alla caviglia Mod "B", con tomaia in pelle fiore e inserti in tessuto cordura. Fodera in tessuto 3D altamente traspirante e assorbente Airnet®. Imbottitura di protezione al malleolo, puntale in Composit®, soletta antiperforazione in materiale tessile Kevlar. Protezione metatarsale rivestita in pelle pieno fiore. Allacciatura mediante lacci passanti in campanelle di metallo (Vis) o fori e sfilamento rapido a clip. Suola in gomma nitrilica con resistenza al calore, antistatica, antiolio e con rilievi antiscivolo. Lavorazione Ago.

Outsole OUAM: Antistatic and anti-slip in nitrile rubber. The Ouam outsole is suitable for

those working outdoors or where high water resistance is required

Upper Leather: Water repellent full-grain leather 1.8-2.0 mm, Cordura fabric: 3D

woven fabric that ensures high breathability

Lining 3D Fabric: AIRNET® - Highly breathable and absorbent three-dimensional mesh

fabric

Insole Textile anti-perforation insole: *Kevlar K18*

Protection Toe cap, anti-perforation midsole and metatarsal protection

Toe cap Composite: resistant up to 200J. Protective strip for toe comfort.

Processing AGO: The Ago processing is the most common because it makes the shoe

flexible and light. The processing consists of joining the upper to the sole

through glues, avoiding the use of other joints that stiffen the structure and lead

to a loss of comfort in the foot

Sector Steelwork, Indoor environments, Building, Mechanical industries

PRODUCT TECHNICAL SHEET



Date 30/11/2025

