

35/1

Norm UNI EN ISO 20345:2022  
Security category S1P  
Additional requirements A, E, HRO, PL, SR, WPA



PRODUCT DESCRIPTION:

Calzatura bassa Mod "A", con tomaia in pelle scamosciata e riporti in cordura. Fodera in tessuto tridimensionale a rete altamente traspirante e assorbente Airnet®. Puntale in Composit®, sottopiede antiperforazione tessile in Kevlar. Allacciatura mediante lacci passanti in fori o in occhielli. Suola in poliuretano con battistrada in gomma nitrilica, antiolio, antistatica e rilievi antiscivolo. Lavorazione Ago.

Lining	3D Fabric: <i>AIRNET® - Highly breathable and absorbent three-dimensional mesh fabric</i>
Size	Unisex 36-49
Processing	<i>AGO: The Ago processing is the most common because it makes the shoe flexible and light. The processing consists of joining the upper to the sole through glues, avoiding the use of other joints that stiffen the structure and lead to a loss of comfort in the foot</i>
Sector	Indoor environments, Manufacturing Industries, Mechanical industries, Textile industries
Footwear type	A (low)
Upper	Suede: <i>Soft calfskin leather</i> , Cordura fabric: <i>3D woven fabric that ensures high breathability</i>
Insole	Anti-perforation: <i>Protects the foot against possible injury caused by the presence of perforating material on the floor.</i>
Toe cap	Composite: <i>resistant up to 200J. Protective strip for toe comfort.</i>
Group	JOGGING
Protection	Toe cap and anti-perforation insole
Outsole	Danilo: <i>Soft cushioning and antistatic polyurethane midsole. Heat resistant rubber tread with high slip resistance even on inclined surfaces.</i>

# PRODUCT TECHNICAL SHEET



Date 06/10/2025

